

VISUS99

Passive infrared motion detector with look-down cover.

FEATURES

- Detection by means of dual pyroelectric sensor immune to temperature changes
- High immunity against false alarms and electromagnetic fields
- Look-down cover
- Manual adjustment of sensibility and thermal compensation of the alarm threshold
- Operating voltage: 10 ÷ 15 Vdc
- Standby current: 12 mA
- Case protection grading: IP50
- Dimensions (WxHxD): 55x91x47 mm



IR360

Designed for applications which require high sensitivity and cover, such as rooms with large amounts of view restricting furniture.

FEATURES

- Ceiling mount for environments with a restricted field of vision
- Digital analysis of the signal for uniform monitoring of the entire field covered
- Temperature compensation for improved performance at critical temperatures
- Sensitivity adjustment to configure the detector for normal or hostile environments
- Excellent RF immunity
- Exceptional white light immunity
- Operating voltage 9.5 ÷ 14 Vdc
- Standby current: 15 mA
- Case protection grading: IP50
- Dimensions (WxHxD): 115x115x25 mm



RILED

Remote LED indicator.

FEATURES

- Supplementary visual signalling for fire and intrusion installation
- Current: max 30mA
- Dimensions (WxHxD): (83x83x26 mm)
- Multi-voltage for intrusion (12V)

